

Safety Data Sheet

[Mixture (Paint)]

1. Products and company identification

| | |
|---|---|
| Product name | EPO ROVAL Thinner |
| Supplier | Roval Corporation |
| Address | 1-1, Nomuramotomachi, Hirakata, Osaka |
| Section in charge | Technical service department |
| Phone number | +81-72-894-7590 |
| Fax number | +81-72-894-7593 |
| e-mail address | jp-info@roval-group.com |
| Emergency Phone Number | +81-72-894-7191 |
| Preparation, revision, and confirmation | May 8, 2023 |
| Product type | Thinner |
| Recommended use | Dilution of paint / Cleaning of paint equipment |

2. HAZARDS IDENTIFICATION

[GHS Classification]

| | | | | | |
|-----------------------------|--|--|-----------------------------------|--|-----------------------------|
| PHYSICAL HAZARDS | | Flammable Liquid | Category 3 | | |
| HEALTH HAZARDS | Acute toxicity | | | | |
| | Oral | Dermal | Inhalation (Gas) | Inhalation (Vapors) | Inhalation (Dust/Mist) |
| | Not calassified | Category 4 | Not calassified | Category 3 | Classification not possible |
| | Skin corosive /irritating | Serious eye damage /eye Irritation | Respiratory/Skin sensitization | | |
| | | | Solid/Liquid | Gas | Skin sensitisation |
| | Category 2 | Category 2 | Classification not possible | Not calassified | Category 1 |
| | Germ cell mutagenicity | Carcinogenicity | Reproductive toxicity | Effects on or via lactation | |
| | Category 2 | Classification not possible | Category 2 | Classification not possible | |
| | STOT (Single exposure) | Category 1 respiratory system | Category 2 central nervous system | Category 3 May cause respiratory irritation May cause drowsiness and dizziness | |
| | STOT (Repeated exposure) | Category 1 central nervous system, skeleton | Category 2 | | |
| Aspiration hazard | Hazardous to the aquatic environment (Acute) | Hazardous to the aquatic environment (Chronic) | Hazardous to the ozone layer | | |
| Classification not possible | Category 3 | Not calassified | Classification not possible | | |

[GHS Symbols]

Pictogram:



Signal word:

DANGER

Hazard statement:

- H225 : Highly flammable liquid and vapour.
- H311 : Toxic in contact with skin.
- H331 : Toxic if inhaled.
- H315 : Causes skin irritation.
- H319 : Causes serious eye irritation.

- H317 : May cause an allergic skin reaction.
- H341 : Suspected of causing genetic defects.
- H361 : Suspected of damaging fertility or the unborn child.
- H370 : Causes damage to organs (central nervous system).
- H371 : May cause damage to organs(central nerve system, kidney, systemic toxicity).
- H335 : May cause respiratory irritation.
- H336 : May cause drowsiness or dizziness.
- H372 : Causes damage to organs (central nerve system, skeleton) through prolonged or repeated exposure.
- H402 : Harmful to aquatic life.

Precautionary Statement:

[SAFETY MEASURES]

- P201 : Obtain special instructions before use.
- P202 : Do not handle until all safety precautions have been read and understood.
- P210 : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P233 : Keep container tightly closed.
- P240 : Ground and bond container and receiving equipment.
- P241 : Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 : Use non-sparking tools.
- P243 : Take action to prevent static discharges.
- P260 : Do not breathe dust/fume/gas/mist/vapours/spray.
- P264 : Wash hands thoroughly after handling.
- P270 : Do not eat, drink or smoke when using this product.
- P271 : Use only outdoors or in a well-ventilated area.
- P272 : Contaminated work clothing should not be allowed out of the workplace.
- P273 : Avoid release to the environment.
- P280 : Wear protective gloves/protective clothing/eye protection/face protection.

[FIRST AID]

- P302+P352 : IF ON SKIN: Wash with plenty water/shower.
- P303+P361+P353 : IF ON SKIN(or hair): Take off immediately all contaminated clothing.
Rinse affected areas with water [or shower].
- P304+P340 : IF INHALED: Remove person to fresh air and Keep comfortable for breathing.
- P305+P351+P338 : IF IN EYES: Rinse cautiously with water for several minutes.
Remove contact lenses,if present and eazy to do. Continue rinsing.
- P308+P313 : IF exposed or concerned: Get medical advice/attention.
- P311 : Call a POISON CENTER or doctor/physician.
- P333+P313 : If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 : If eye irritation persists: Get medical advice/attention.
- P362+P364 : Take off contaminated clothing and wash it before reuse.
- P370+P378 : In case of fire: Use carbon dioxide, foam, powder, dry sand, or atomized reinforcing liquid to extinguish.

[STORAGE]

- P403+P233 : Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 : Store in well-ventilated place. Keep cool.
- P405 : Store locked up.

[DISPOSAL]

- P501 : Appropriately dispose of the contents/containers in accordance with laws and regulations.

3. Composition/information on ingredients

Distinguishing Chemicals and Mixtures: Mixtures

| Substance name | % Weigh | CAS No. |
|----------------|---------|----------|
| Butyl acetate | 40 ~ 45 | 123-86-4 |
| Cyclohexanone | 55 ~ 60 | 108-94-1 |

4. First-aid measures

Inhaled:

Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Contact a doctor when you feel ill.

Skin contact:

Wipe off the adherent quickly with a cloth.

Wash with plenty of water.

Do not use solvents or thinners.

Seek medical attention / treatment if skin irritation or rash occurs.

Take off contaminated clothing and Wash it before reuse.

If it gets on the skin (or hair): Contact your doctor immediately. Remove all contaminated clothing immediately.

Wash skin with water or shower.

Eye contact:

Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Consult a doctor immediately.

If eye irritation persists: Get medical advice/attention.

If on clothing:

Rinse immediately contaminated clothing and skin with plenty of water before removing clothes.

Swallowed:

If swallowed incorrectly, allow the patient to rest and consult a physician immediately.

Do not induce vomiting.

Emergency measures:

Wear appropriate protection equipment (e.g. protective glasses, protective masks, gloves, etc.).

Ventilation is performed.

5. Fire-fighting measures

Suitable extinguishing agents:

Carbon dioxide, foam, powder, dry sand, and atomized reinforcing liquid.

Fire extinguishing agents not to be used:

Water (rod-shaped water, high-pressure water)/rod-shaped reinforcing liquid.

Special methods for extinguishing fires, protection of persons who extinguish fires:

Wear proper protective equipment.

Quickly remove flammable materials from the surroundings if safe to deal with.

Use specified extinguishing media.

Cool closed containers which may be exposed to heat.

Extinguish from windward side.

6. Accidental release measures

Precautions for the Human Body, Protective Equipment, and Emergency Measures:

Appropriate protective equipment (protective gloves, protective masks, aprons, goggles, etc.) should be worn during work.

Ventilating firmly indoors In outdoor cases, work from the windward as much as possible.

Prevent secondary disasters by prohibiting access to the surrounding area and keeping other people away.

Avoid sparks, flames and anything which can cause fire.

Prepare extinguishing media for accidental fire.

Environmental precautions:

Be careful not to cause environmental effects due to discharge into rivers, etc.

Containment and Purification Methods and Equipment:

For small spill, absorb spills with inert materials, then place in a chemical waste containers.

Disposal of deposits, waste, etc. shall be made in accordance with relevant laws and regulations.

Collect by using a tool made of a material that does not generate sparks due to impact or static electricity.

Absorb in dry sand, soil, or other non-combustible materials for recovery.

A large amount of leakage is prevented by surrounding with embankment.

7. Handling and storage

Handling:

Handle in a well-ventilated area.

The container is sealed each time.

Keep away any source of flame, sparks, and heat.

Wear antistatic cloths and shoes.

Use sparkless equipment.

For countermeasures against static electricity, the equipment, etc. shall be grounded, and explosion-proof type shall be used for the electrical equipment, etc.

Used waste, paint waste, spray dust, etc. should be kept in water until discarded.

Wear protective equipment to keep skin, mucous membranes, or clothing from touching or coming into the eyes.

Wash hands and face completely after the handling.

Handle in a well-ventilated area. Wear personal protective cloths.

Storage:

Avoid direct sunlight. Store in a dry, well-ventilated area.

Take necessary measures to prevent leakage, overflow, or splashing.

Keep locked to prevent theft.

Keep out of the reach of children.

Keep containers away from fire/flame.

8. Exposure controls/personal protection

| Substance name | ACGIH |
|----------------|--------------|
| Butyl acetate | 150 ppm(TWA) |
| Cyclohexanone | 25 ppm(TWA) |

[Equipment Measures]

Use air extractors to prevent fume formation. Use air extractors to prevent fume formation.

Equipment for transporting, pumping, agitation, etc. of liquids shall be equipped to be grounded.

Equipment shall be installed in the vicinity of the handling site so as not to be subject to high temperatures or ignition sources.

In the case of indoor painting work, equipment that does not expose workers directly, such as by using automatic painting machines, etc., or equipment that avoids workers from exposure by local exhaust ventilation systems, etc., shall be used.

When working in a sealed place such as the inside of a tank, install a device that can sufficiently ventilate to the bottom of the sealed place.

[Protection]

Respiratory protection:

Wear gas masks for organic gases.

In cases of inadequate ventilation, a respiratory protective device should be worn to prevent overexposure.

Hand protection:

Wear gloves made of organic solvents or chemicals that do not penetrate.

Eye protection:

Wear protective glasses for handling.

Skin and body protection:

When handled, wear clothing that does not directly expose the skin.

Further, it is desirable that the material is a material that does not permeate the chemical.

Other:

Wear antistatic clothing and electrostatic shoes when performing electrostatic painting operations.

9. Physical and Chemical Properties and safety characteristics

| | | | |
|---------------------------|-------------------|---------------------------|---------------------------|
| Physical state | :Liquid | Colour | :Clear and colorless |
| Odor | :Solvent odor | Boiling point | :126°C~156°C |
| Flammability | :Flammable Liquid | Explosion Limits | :LEL 1.1vol% UEL 9.4vol % |
| Flash point | :32.7°C | Auto-ignition temperature | :420°C |
| Decomposition temperature | :No data | Kinematic viscosity | :No data |
| Vapor pressure | :No data | Densities (g/ml) | :0.92 |
| Relative vapour density | :No data | | |

10. Stability and Reactivity

Reactivity: No self-reactivity.

Chemical Stability: Stable in normal handling.

Hazardous Reaction Potential: No data.

Conditions to avoid: Heating, high temperature, contact with incompatible substances.

Forming of mixture with atmosphere within flammable limit.

Incompatible substances: Risk of reacting on contact with oxidizing substances, water, etc.

Hazardous decomposition products: Heat decomposition produces carbon monoxide, carbon dioxide. Generate stimulant gas.

11. Toxicological information

ACUTE TOXICITY

| Substance name | Oral | Classification | Dermal | Classification |
|----------------|---------------|-----------------|--------------|-----------------|
| Butyl acetate | 10.736 g / kg | Not calassified | > 5.0 g / kg | Not calassified |
| Cyclohexanone | 1.296 g / kg | Category 4 | 0.947 g / kg | Category 3 |

ACUTE TOXICITY

| Substance name | Inhalation (Gas) | Classification | Inhalation (Vapors) | Classification | Inhalation (dust, mist) | Classification |
|----------------|------------------|----------------|-----------------------------|----------------|-----------------------------|-----------------|
| Butyl acetate | Not calassified | | Classification not possible | | Classification not possible | |
| Cyclohexanone | Not calassified | | 2450 ppm | Category 3 | 8000 ppm | Not calassified |

| Substance name | Skin corrosive/Irritating | Serious eye damage /eye Irritation | Respiratory sensitisation | Skin sensitisation |
|----------------|---------------------------|------------------------------------|-----------------------------|-----------------------------|
| Butyl acetate | Not calassified | Category 2B | Classification not possible | Classification not possible |
| Cyclohexanone | Category 2 | Category 2A | Classification not possible | Category 1 |

| Substance name | Germ cell mutagenicity | Carcinogenicity | Reproductive toxicity |
|----------------|-----------------------------|-----------------------------|-----------------------------|
| Butyl acetate | Classification not possible | Classification not possible | Classification not possible |
| Cyclohexanone | Category 2 | Not calassified | Category 2 |

| Substance name | STOT (Single exposure) | STOT (Repeat exposure) | Aspiration hazard |
|----------------|--|---|-----------------------------|
| Butyl acetate | Category 3 (irritating to the respiratory tract, anaesthetic effect) | Classification not possible | Classification not possible |
| Cyclohexanone | Category 1 (respiratory system) | Category 1 (central nervous system, bone) | Classification not possible |
| | Category 2 (central nervous system) | | |
| | Category 3 (anaesthetic effect) | | |

1 2. Ecological information

General precautions: When leaking or disposing of the product, be careful to handle it because it may affect the environment.

The product may have adverse effect on environment.

| Substance name | Hazardous to the aquatic environment(Acute) | Hazardous to the aquatic environment (Chronic) | Hazardous to the ozone layer |
|----------------|---|--|------------------------------|
| Butyl acetate | Category 3 | Not calassified | Classification not possible |
| Cyclohexanone | Not calassified | Not calassified | Classification not possible |

Ecotoxicity:

No data

Persistence and degradability:

Has rapid decomposition (degree of degradation by BOD: 98%) «Butyl acetate»

Bioaccumulation:

May be low potential (log K_{ow} = 1.78) «Butyl acetate»

Mobility in soil:

No data

1 3. Disposal considerations

[Residual Waste, Contamination Containers and Packaging]

In the case of disposal, the relevant laws and regulations and the standards of local governments shall be complied with. Waste including residue and container should be disposed by licensed industrial waste disposer after the consignment contract. Wash water used for cleansing containers and equipment must not be released into environment. For other wastage arouse in effluent processing or incineration, dispose of them in accordance with the law or entrust it. Dispose of the empty container after the rest of paint completely removed. It is recommended to recycle empty containers and packaging. When there is a possibility of generating toxic gases such as dioxin, enter into a contract with a licensed industrial waste disposal company and dispose of it.

Dispose of the empty container after the rest of paint completely removed. Empty container should be disposed of by industrial waste disposal contractor after the consignment contract.

1 4. Transport information

UN No. 1263 Proper shipping name: Paint or Paint related material Hazard class: 3 PG :III

Special precautions for transport or means of transport:

Follow the instructions in the Handling and Storage Precautions section.

Check that there is so leaking in the container,and load.

Prevent collapse of the container so that there is no falling or damage.

[Regulations]

Land transport:

Follow the transport methods stipulated in the Fire Service Law and the Industrial Safety and Health Law, if applicable.

The consignor shall issue the Carriage Precautions (Yellow Card) to the Carrier.

Maritime transport:

In accordance with the Ship Safety Law.

Air transport:

In accordance with the provisions of the Aeronautical Law.

1 5. Regulatory information

Classification and labeling in accordance with Labor Safety and Health Act:

See Section 2

Other regulation for foreign countries:

Regulatory information with regards to this preparation in your country or region should be examined by your own responsibility.

1 6 . Other information

References:

- 1) GHS Classification Guidance for Enterprises.
- 2) SDS from manufacturers of raw materials.
- 3) Roval's own data.

The information herein is given in good faith, but no warranty, express or implied, is made.

The information contained herein is, to the best of Roval's knowledge and belief, accurate and reliable as of the data issued. It is the user's responsibility to determine the suitability of this information for the adoption of necessary safety precautions. We reserve the right to revise SDS periodically as new information becomes available.